



AUXQUIMIA
Fire fighting products

**THE
FOAM
SOLUTION**



AQUAFILM™ AF-1 ICAO B

PREMIUM FOAM CONCENTRATE AFFF 1%

Aquafilm™ AF-1 ICAO B is specifically designed to fight effectively all type of Class B fires (Hydrocarbon) being also very adequate to fight Class A fires.

Its extraordinary AFFF properties give this product an effective and rapid knockdown of the fire when fighting non miscible flammable liquids. **This product is specially designed to fulfill and exceed aviation requirements.**

Aquafilm™ uses very specific fluorinated and hydrocarbon surfactants in order to allow a good formation of an aqueous film on the surface of most hydrocarbon fuels, suppressing vapour leaks and preventing its contact with the oxygen and providing an excellent sealing on hot surfaces. Its formulation allows a great oil repellence, fluidity and burnback resistance.

Aquafilm™ is a perfect tool to fight fires on storage tanks, bund, process areas, loading racks, power stations, airports or marine terminals amongst others.

Aquafilm™ is designed to be used with low expansion foam equipment (nozzles, monitors, foam chambers, etc.), non-as-

pirating devices (water spray nozzles and standard sprinklers) and medium expansion foam branches.

Aquafilm's AF-1 ICAO B dilution rate is 1% to perform extraordinarily on fresh or sea water. It may be proportioned with standard equipment (in-line inductors, bladder tanks, balanced pressure systems, etc.) and special purpose ones for AFFF agents (e.g. Hydrofoam nozzles).

Aquafilm is highly biodegradable and it is manufactured according to "C6 fluorocompounds" fulfilling the 2010/2015 EPA PFOA Stewardship Program.

A-33018003

AUXQUIMIA S.A.U.

Polígono de Baiña, parcela 23
33682 Mieres (Asturias). Spain

T (+34) 985 242 945 / 946. F (+34) 985 253 809

24H EMERGENCY
(+44) 01202864796

auxquimia.com



Perimeter SOLUTIONS
perimeter-solutions.com



AQUAFILM™ AF-1 ICAO B

PREMIUM FOAM CONCENTRATE AFFF 1%

SPECIFICATIONS

| CONCENTRATE | |
|---|------|
| Specific gravity @ 20°C | 1.03 |
| pH @ 20°C | 7.5 |
| Viscosity, cone and plate, mPa.s @ 20°C | 11 |
| Freezing point, °C | <-10 |
| Lowest temp. for use, °C | -10 |

| FOAM SOLUTION | |
|---|------|
| Dilution rate | 1% |
| Surface tens. at 20°C, mN/m (Demineralised water) | 16.0 |
| Interfacial tens. with cyclohexane at 20°C, mN/m | 3.0 |
| Low Expansion Foam (EN-1568-3) | |
| Foam Expansion Index | 8.5 |
| 25% Drainage Time, min:s | 3:00 |

PERFORMANCE

The foam achieves a very quick knock-down of fires, even with low application rates, and shows an excellent burn-back resistance. It is certified according to EN-1568-3:2008 (class 1B). The product is also certified according to ICAO Level B.

| Standard | EN-1568-3:2008 | | ICAO B |
|------------------|----------------|--------|--------------|
| Fuel | Heptane | | Kerosene |
| Application | Forceful | Gentle | Forceful |
| Dilution rate, % | 1 | 1 | 1 |
| Water | Fresh | Fresh | Fresh |
| Extinction | 0:59 | 1:25 | 0:45 |
| Burnback 25% | <10:00 | 16:15 | 18:00 |
| Classification | 1B | | Pass level B |

EN 1568:
2008 Part 3



PACKING

The product is supplied in 20 or 25 L PE prismatic containers, 200 L PE cylindrical drums and 1.000 L IBC containers.

STORAGE

The concentrate should be stored at temperatures between -10° and +50°C, preferably in the original containers or in stainless steel or epoxy lined tanks. Avoid permanent contact with carbon steel, iron, copper alloys, aluminium, etc. Do not mix with other foam concentrates without a previous verification of compatibility.

CAUTIONS

Foams should not be used in contact with electrical equipment nor with chemical products that can react with water. It is recommended to avoid the contact of the foam concentrate with the skin. In case of eye splashes wash with plenty of water. In case of ingestion do not induce vomit, drink water and take medical advice.