



AUXQUIMIA
Fire fighting products

**THE
FOAM
SOLUTION**



AQUAFILM™ ARN-0,5

PREMIUM Newtonian (Low Viscosity) AFFF-AR Foam Concentrate

Aquafilm™ ARN-0,5 is a low viscosity AFFF foam compounds to fight polar and no polar fuel fires. The resistance against the typical destructive effect of the polar liquids on foams is achieved thanks to the nature of the special surfactants used in the composition, avoiding the use of polymers which increase viscosity and make difficult the dosage at low temperatures. Aquafilm™ ARN solves all these issues you might encounter with higher viscosity products.

Aquafilm™ ARN-0,5 uses very specific fluorinated and hydrocarbon surfactants in order to allow a good formation of an aqueous film on the surface of most hydrocarbon fuels, suppressing vapour leaks and preventing its contact with the oxygen and providing an excellent sealing on hot surfaces. Its formulation allows a great oil repellence, fluidity and burnback resistance.

Aquafilm™ ARN-0,5 is a perfect tool to fight fires on storage tanks, bund, process areas, loading racks, power stations, airports or marine terminals amongst others.

Aquafilm™ ARN-0,5 should be applied with low and medium expansion foam equipment (nozzles, monitors, foam chambers, etc.)

On hydrocarbon fires it can be applied also with non-aspirating devices (water spray nozzles and standard sprinklers). The foam has a very good resistance to all kind of chemicals. The dilution rate is 0,5% in fresh or sea water for use on all

kind of fuels: hydrocarbon and polar solvents. It may be proportioned with standard equipment (in-line inductors, bladder tanks, pumps, balanced pressure systems, etc.) and special purpose ones for AFFF agents (e.g. Hydrofoam nozzles). Its low viscosity facilitates the dosage at low temperatures, until -20°C.

Aquafilm™ ARN-0,5 is highly biodegradable and it is manufactured according to "C6 fluorocompounds" fulfilling the 2010/2015 EPA PFOA Stewardship Program.

A-33018003

AUXQUIMIA S.A.U.

Polígono de Baiña, parcela 23
33682 Mieres (Asturias). Spain

T (+34) 985 242 945 / 946. F (+34) 985 253 809

24H EMERGENCY
(+44) 01202864796

auxquimia.com



Perimeter SOLUTIONS
perimeter-solutions.com



AQUAFILM™ ARN-0,5

PREMIUM Newtonian (Low Viscosity) AFFF-AR Foam Concentrate

SPECIFICATIONS

CONCENTRATE	
Specific gravity @ 20°C	1.1
pH @ 20°C	8.5—9
Viscosity, cone and plate, mPa.s @ 20°C	55
@ 0°C	150
Freezing point, °C	< -20
Lowest temp. for using, °C	-20

FOAM SOLUTION	
Dilution rate	0.5%
Surface tens. at 20°C, mN/m (Demineralised water)	17.3
Interfacial tens. with cyclohexane at 20°C, mN/m	3.0
Low Expansion Foam (EN 1568-3)	
Foam Expansion Index	7
25% Drainage Time, min:s	2:30

PERFORMANCE

The foam achieves a very quick knock-down of fires, even with low application rates, and shows an excellent burn-back resis-

tance. The product fulfils the standard **EN 1568-3 (class IC)** and **EN 1568-4 (class IB)**.

Standard	EN-1568-3		EN-1568-4
Fuel	Heptane		Acetone
Application	Forceful	Gentle	Gentle
Dilution rate, %	0.5	0.5	0.5
Water	fresh	fresh	fresh
Extinction	1:50	2:30	1:30
Burnback 25%	-	11:30	11:00
Classification	IC		IB

EN 1568:
2008 Parts 3&4

PACKING

The product is supplied in 20 or 25 L PE prismatic containers, 200 L PE cylindrical drums and 1.000 L IBC containers.

STORAGE

The concentrate should be stored at temperatures between -20°C and +50°C, preferably in the original containers or in stainless steel or epoxy lined tanks. Avoid permanent contact with carbon steel, iron, copper alloys, aluminium, etc. Do not mix with other foam concentrates without a previous verification of compatibility.

CAUTIONS

Foams should not be used in contact with electrical equipment nor with chemical products that can react with water. It is recommended to avoid the contact of the foam concentrate with the skin. In case of eye splashes wash with plenty of water. In case of ingestion do not induce vomit, drink water and take medical advice.