

# AQUAFILM™ EXD-20

## AFFF FOAM SOLUTION (-20°C)



### DESCRIPTION

Aqueous solution of an AFFF agent specifically designed for its use in aerosols. Contains solvents and salts to decrease the freezing point below -20 °C. making it suitable for its use in cold climates.

### USE

AQUAFILM EXD-20 can be used directly in any foaming or spraying system, but it has been especially designed as fluid for recharging extinguishers. When it is used to fight hydrocarbon fires, it is capable of achieving very fast extinctions and the foam that remains on fuel, provides a good protection against possible burn-back. It can be used also for class F fires.

### DOSAGE

The product must be used directly.



### SPECIFICATIONS

FOAM SOLUTION	
Density @ 20°C, gr/cm <sup>3</sup>	1.14
pH @ 20°C	7.0±0.5
Viscosity, mPa.s @ 20°C	7
Freezing point, °C	<-20
Surface tens. at 20°C, mN/m (Demineralised water)	17.5±0.5
Interfacial tens. with cyclohexane at 20°C, mN/m	1.5±0.5
Low Expansion Foam (EN 1568-3)	
Foam Expansion Index	8
25% Drainage Time, min:s	8:00

**PERFORMANCE**

A 9 lit. hand extinguisher loaded with AQUAFILM EXD-20 extinguishes easily the 144B fire test (4,5 m2).

**PACKAGING**

The product is supplied in 200 L PE cylindrical drums and 1.000 L IBC containers.

**STORAGE**

The product should be stored at temperatures between -20° and +50°C, preferably in its original containers or in stainless steel or epoxy lined tanks. Do not mix with other products without a previous verification of compatibility.

**⚠ CAUTIONS**

Foams should not be used in contact with electrical equipment neither with chemical products that can react with water. It is recommended to avoid the contact of the foam concentrate with the skin. In case of eye splashes, wash with plenty of water. In case of ingestion do not induce vomit, drink water and take medical advice.

**Solutions That Save.****FOR MORE INFORMATION**

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:

[www.Perimeter-Solutions.com](http://www.Perimeter-Solutions.com)

**UNITED STATES**

1520 Brookfield Avenue  
Green Bay, WI 54313

Tel: +1 (920) 593-9445

[salesfoamusa@perimeter-solutions.com](mailto:salesfoamusa@perimeter-solutions.com)

**EMEA**

Polígono Industrial de Baiña, Parcela 23  
33682 Baiña-Mieres (Asturias) – Spain

Tel: +34 985 24 29 45

[salesfoamemea@perimeter-solutions.com](mailto:salesfoamemea@perimeter-solutions.com)

**ASIA PACIFIC**

3 Charles Street  
St Marys NSW 2760 – Australia

Tel: +61 2 9673 5300

[salesfoamapac@perimeter-solutions.com](mailto:salesfoamapac@perimeter-solutions.com)

[perimeter-solutions.com](http://perimeter-solutions.com)

**NOTICE** PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.