

SOLBERG® SELF-EDUCTING FOAM NOZZLE - TFT

DESCRIPTION

The Task Force Tips® MASTER FOAM nozzle is a simple and rugged self-educating foam nozzle with superior stream quality and reach. This fixed flow fog nozzle rated at 100 psi (7 bar) is available with an optional flow rate of 250, 350, 500, 750 or 1000 gpm (946, 1325, 1893, 2839, 3785 l/min). Fog angle is user adjustable between 90° wide fog and straight stream. The nozzle's baffle is easily removed for flushing debris. The standard swivel coupling is 2.5" NH, NPSH, or BSP (65 mm) female threads.

The simple flow geometry (patent pending) can educt foam concentrate at .5%, 1 %, 3%, or 6% with no small passages to clog. Percentage is easily set with an interchangeable orifice plate. A set of calibrated foam orifice plates is included. Nozzle comes with an industrial grade UV resistant, 8 feet long, 1.5" diameter (2.4 m x 38 mm) concentrate hose with a cam lock fitting for quick and secure attachment to the nozzle. The simple and basic design requires no grease or other maintenance. The halo ring/stream shaper is made from non-corrosive high temperature polymer. The rubber bumper is UV resistant. The MASTER FOAM self-educating nozzle is available in hardcoat anodized ANSI A356.0.T6 aluminum. All MASTER FOAM nozzles accept the FJ-LX-M FOAMJET low expansion air-aspirating attachment.




SPECIFICATIONS

K-factor	500 gpm at 100 psi - K-factor= 50 (1893 l/min at 7 bar)
Flow Rate	500 gpm (1893 l/min)
Pressure	100 psi (7 bar)
Flow Control Method	Fixed flow at a pressure (constant flow rate; flow does not change with pattern)
Coupling Size (Nozzles)	2.5 inch (65 mm)
Coupling Style (Nozzles)	Rocker
Coupling Swiveling/Rigid (Nozzles)	Swivel (non-full time, no swivel after tightening)
Pattern Actuation Method	Manual with Halo
Certifications	N/A

SOLBERG® SELF-EDUCTING FOAM NOZZLE - TFT

DIMENSIONAL INFORMATION

ZMFA



1.5" Diameter concentrate hose with one 1.5" cam lock fitting, one 2" cam lock fitting. Industrial grade, UV resistant, 10 feet (3 m) long.

.5% 1% 3% 6%
 Calibrated foam orifice plates




Dust cap with cam lock fitting

THREADS (SWIVEL) 2.5" (65 MM)

FLOW @ 100 PSI (7 BAR)

1) 2.5" - 7.5 NH Female	0) 250 gpm (946 l/min) - K-factor= 25
2) 2.5" - 11 BSP Female	1) 350 gpm (1325 l/min) - K-factor= 35
3) 2.5" - 11.5 NPSH Female	2) 500 gpm (1893 l/min) - K-factor= 50
4) 2.5" SPECIAL THREADS	3) 750 gpm (2839 l/min) - K-factor= 75

ZMF



2" Diameter concentrate hose with one 1.5" cam lock fitting, one 2" cam lock fitting. Industrial grade, UV resistant, 10 feet (3 m) long.

1% 3%
 Calibrated foam orifice plates



Dust cap with cam lock fitting

THREADS (SWIVEL) 2.5" (65 MM)

FLOW @ 100 PSI (7 BAR)

1) 2.5" - 7.5 NH Female	4) 1000 gpm (3785 l/min) - K-factor= 100
2) 2.5" - 11 BSP Female	5) 1250 gpm (4732 l/min) - K-factor= 125
3) 2.5" - 11.5 NPSH Female	
4) 2.5" SPECIAL THREADS	

ORDERING INFORMATION

SELF-EDUCTING NOZZLES

APPROXIMATE SHIPPING WEIGHT

PART NO.	DESCRIPTION	lb	kg
32243	Self-Educting Nozzle - TFT, 250 gpm (946 l/min), 2.5" - 7.5 NH female inlet	7	3
32240	Self-Educting Nozzle - TFT, 350 gpm (1325 l/min), 2.5" - 7.5 NH female inlet	7	3
32241	Self-Educting Nozzle - TFT, 500 gpm (1893 l/min), 2.5" - 7.5 NH female inlet	7	3
32242	Self-Educting Nozzle - TFT, 750 gpm (2839 l/min), 2.5" - 7.5 NH female inlet	7	3
32244	Self-Educting Nozzle - TFT, 1000 gpm (3785 l/min), 2.5" - 7.5 NH female inlet	7	3



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:

www.Perimeter-Solutions.com

UNITED STATES

10667 Jersey Blvd.
Rancho Cucamonga, CA 91730
Tel: +1 800 682 3626
Tel: +1 909 983 0772
salesfoamusa@perimeter-solutions.com

EMEA

Polígono de Baiña, Parcela 23
33682 Mieres (Asturias)
Spain
Tel: +34 985 24 29 45
salesfoamemea@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street
St Marys NSW 2760 – Australia
Tel: +61 2 9673 5300
salesfoamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.