

# PHOS-CHEK® LC95

LONG-TERM FIRE RETARDANT  
LOW/MEDIUM VISCOSITY  
LIQUID CONCENTRATE  
(LC95A-R, LC95A-Fx, LC95W)



## APPLICATIONS

**PHOS-CHEK® LC95A-R** fire retardants are qualified by the USDA Forest Service under specification 5100-304c for use in fixed-wing air tankers, helicopters with buckets and ground engines. PHOS-CHEK LC95A-R is ideal for use in multi-engine, fixed-wing air tankers and single-engine air-tankers. The concentrate is delivered to the using location as a low or medium viscosity liquid and is stored in the concentrate form. It is diluted and mixed with water as it is transferred to the delivery system. PHOS-CHEK LC95A-R and PHOS-CHEK LC95A-Fx are colored to provide effective aerial application. PHOS-CHEK LC95A-Fx provides ultra-high visibility when dropped. Both retardants fade after exposure to sunlight. Uncolored PHOS-CHEK LC95W is ideal for ground application where color is not required or is undesirable.

PHOS-CHEK fire retardants are used for wildland fire control in forest, brush or grassland. Functionally, PHOS-CHEK retardants react with and alter the thermal decomposition of wildland fuels so that they do not support flaming or glowing combustion. This deprives the fire of fuel, reducing fire intensity and the rate of flame spread. LC95 fire retardant is also useful for prescribed burns. When applied at low application rates, fire intensity is dramatically decreased while slow burning is allowed.



## DESCRIPTION

**PHOS-CHEK LC95** fire retardants are concentrated liquids that mix readily with water by recirculation, agitation or with mechanical or electronic PHOS-CHEK liquid proportioning systems. PHOS-CHEK LC95 fire retardant and variants are the only liquid concentrate (LC) ammonium polyphosphate retardants that offer both the ease of mixing and handling of a liquid and the aerial drop advantages of a gum-thickened retardant. The elastic nature of the thickener in PHOS-CHEK retardants reduces drift, dispersion and evaporation and facilitates increased fuel coverage, wrap around and penetration through canopy and ladder fuels to ground vegetation. Recovery can exceed 90%.

PHOS-CHEK LC95 is available in Red Iron Oxide (R), Fugitive (F) and Uncolored (W). The fugitive color maintains visibility during application, but slowly fades after exposure to sunlight. PHOS-CHEK LC95A-R is available as low viscosity or medium viscosity. Medium viscosity is ideal for higher altitude drops or where higher coverage levels are desired.



**PHOS-CHEK®  
LC95**

**LONG-TERM FIRE RETARDANT  
LOW/MEDIUM VISCOSITY LIQUID CONCENTRATE  
(LC95A-R, LC95A-Fx, LC95W)**

**APPLICATIONS**

	RETARDANT	GEL	FOAM	WATER
Indirect Attack	✓✓✓✓	✓✓	✓	
Direct/Parallel Attack	✓✓✓✓	✓✓✓	✓✓	✓
Interior Structure Attack		✓✓	✓✓✓✓	✓
Structure Protection: - Indirect Application	✓✓✓✓	✓✓✓	✓✓	✓
Structure Protection: - Direct Application		✓✓✓✓	✓✓✓	✓
Mop Up	✓✓	✓✓	✓✓✓✓	✓
Prescribed Burn Control	✓✓✓✓	✓✓✓	✓✓	✓

✓✓✓✓ = Superior Effectiveness  
 ✓✓✓ = Excellent Effectiveness  
 ✓✓ = Good Effectiveness  
 ✓ = Baseline Effectiveness

**PRODUCT CHARACTERISTICS**

Color/Odor	Red (R), Fugitive (F), Uncolored (W)
Mix Ratio	5.5 gal of water/gal concentrate
Yield	1054 gal/ton of concentrate, 4398 litres/metric ton of concentrate
Concentrate Density	12.29 lb/gal, 1,476 kg/litre
Solution Density	8.97 lb/gal of mixed retardant, 1,077 kg/litre
Viscosity	100 - 400 centipoise (cP)
Refractive Index	12.75 - 14.50



# PHOS-CHEK® LC95

## LONG-TERM FIRE RETARDANT LOW/MEDIUM VISCOSITY LIQUID CONCENTRATE (LC95A-R, LC95A-Fx, LC95W)

### PACKAGING

ORDERING INFORMATION			
PHOS-CHEK LC95-R RETARDANT	lb*	kg*	Part #
PHOS-CHEK LC95A-R Retardant 5 gallon pail (20 litres)	61	28	10003939
PHOS-CHEK LC95A-R Retardant 55 gallon drum (200 litres)	677	307	10002792
PHOS-CHEK LC95A-R Retardant 260 gallon tote (984 litres)	3203	1453	10003222
PHOS-CHEK LC95A-R Retardant Bulk	—	—	10001554
PHOS-CHEK LC95-Fx Retardant	lb*	kg*	Part #
PHOS-CHEK LC95A-Fx Retardant 5 gallon pail (20 litres)	61	28	10004605
PHOS-CHEK LC95A-Fx Retardant 55 gallon drum (200 litres)	672	305	10004842
PHOS-CHEK LC95A-Fx Retardant 260 gallon tote (984 litres)	3177	1441	10004595
PHOS-CHEK LC95A-Fx Retardant Bulk	—	—	10004642
PHOS-CHEK LC95W Retardant	lb*	kg*	Part #
PHOS-CHEK LC95W Retardant 5 gallon pail (20 litres)	61	28	10002983
PHOS-CHEK LC95W Retardant 55 gallon drum (200 litres)	677	307	10004780
PHOS-CHEK LC95W Retardant 260 gallon tote (984 litres)	3200	1451	10003107
PHOS-CHEK LC95W Retardant Bulk	—	—	10002883

\*Approximate shipping weight

Contact your local authorized PHOS-CHEK distributor or factory sales representative for additional details. [perimeter-solutions.com](http://perimeter-solutions.com)

### HANDLING PRECAUTIONS

- For detailed safety information, please refer to the SDS.
- Minimally irritating to the eyes, non-irritating to skin.
- **Precautionary Measures:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary contact and removal of the material from the eyes, skin and clothing.
- **Eye Protection:** As a good industrial practice, the use of chemical goggles is recommended. Eye flushing equipment should also be available.
- **Skin Protection:** As a good industrial practice, wear protective gloves to minimize skin contact. Wash hands and contaminated skin after handling.
- **Respiratory Protection:** Wear dust mask if dusty conditions exist. Avoid breathing vapor or mist.
- For complete SDS, visit [perimeter-solutions.com](http://perimeter-solutions.com)



## Solutions That Save.

### FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:

[www.perimeter-solutions.com](http://www.perimeter-solutions.com)

### UNITED STATES

1520 Brookfield Avenue  
Green Bay, WI 54313  
Tel: +1 (920) 593-9445  
[salesfoamusa@perimeter-solutions.com](mailto:salesfoamusa@perimeter-solutions.com)

### EMEA

Polígono Industrial de Baiña, Parcela 23  
33682 Baiña-Mieres (Asturias) – Spain  
Tel: +34 985 24 29 45  
[salesfoamemea@perimeter-solutions.com](mailto:salesfoamemea@perimeter-solutions.com)

### ASIA PACIFIC

3 Charles Street  
St Marys NSW 2760 – Australia  
Tel: +61 2 9673 5300  
[salesfoamapac@perimeter-solutions.com](mailto:salesfoamapac@perimeter-solutions.com)

[perimeter-solutions.com](http://perimeter-solutions.com)

**NOTICE** PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.