

ARCTIC™ 1x3% FREEZE PROTECTED ATC™ FOAM CONCENTRATE

TYPICAL PHYSICAL PROPERTIES

AT 77 °F (25 °C)

Appearance: Pale straw colored gelled liquid

Freezing Point: -25°F (-32°C)
(No quality loss after thawing)

Maximum Storage Temp: 120°F (49°C)

pH: 7.0 - 8.5

Refractive Index: 1.3960 - 1.4010

Specific Gravity: 1.032 - 1.072

Viscosity: 2300 - 3300 cP*

Sediments: < 0.05%

* Brookfield Viscometer Spindle #4,
Speed 30 rpm

APPLICATION

ARCTIC 1x3 FP ATC foam concentrate can be applied to either Class B hydrocarbon or polar solvent fuel fires. The product is mixed 1 part foam concentrate to 99 parts water for hydrocarbon fuels or 3 parts foam concentrate to 97 parts water for polar solvent fuels. It may also be used as either a 1% or 3% pre-mix solution. The foam can be used to prevent re-ignition of a liquid spill and control hazardous vapors. Foam discharge devices such as non-air aspirating, as well as, air aspirating ARCTIC™ 1x3% FREEZE PROTECTED ATC™ FOAM CONCENTRATE equipment can be used to obtain maximum results. ARCTIC 1x3 FP ATC foam is compatible with most powder (dry chemical) agents.

PERFORMANCE

Foam Proportioning

ARCTIC 1x3 FP ATC foam concentrate can be proportioned at the proper foam solution percentage using most common proportioning devices such as:

- Eductors
- Inline balance pressure proportioners
- Ratio controllers
- Self-inducting nozzles



DESCRIPTION

ARCTIC™ 1x3 FP ATC™ foam concentrate is a freeze protected, synthetic, alcohol-resistant foam concentrate used to effectively extinguish Class B hydrocarbon fuel fires at 1% and polar solvent fuel fires at 3%. ARCTIC 1x3 FP ATC foam provides rapid extinguishment and excellent burn back characteristics and can be proportioned at 1% or 3% solution in fresh, salt and brackish water.

STORAGE

The storage temperature range for ARCTIC 1x3 FP ATC foam concentrate is -20 °F to 120 °F (-29 °C to 49 °C).

When stored in original containers or in manufacturer recommended equipment and within the specified temperature range, the shelf life is 20 years.

COMPATIBILITY

ARCTIC 1x3 FP ATC foam concentrate should not be mixed with other foam concentrates. For questions about compatibility or mixing of foam concentrates, consult Perimeter Solutions Technical Services.

Materials of Construction Capability

ARCTIC 1x3 FP ATC foam concentrate is compatible with multiple materials of construction like carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate. For questions about material compatibility, consult Perimeter Solutions Technical Services.

INSPECTION

ARCTIC 1x3 FP ATC foam concentrate or pre-mix solutions should be inspected annually per National Fire Protection Association (NFPA) Standards 11 and 25. A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA 11.

CERTIFICATIONS

Solberg manufactured products are thoroughly inspected and undergo rigorous quality control tests. These evaluations analyze the foam's physical parameters and the finished product's fire performance. A Certificate of Analysis (CoA) is issued with every batch.

ARCTIC™ 1X3% FREEZE PROTECTED ATC™ FOAM CONCENTRATE

ORDERING INFORMATION

ARCTIC 1x3 FP ATC foam concentrate is available in pails, drums, totes and bulk quantities.

ORDERING INFORMATION

Part No.	Description	Approximate Shipping Weight	Approximate Cube
20250	ARCTIC 1x3 FP ATC, 5 gallon (20 litre) pail	45 lb (21 kg)	1.25 ft ³ (0.04 m ³)
20251	ARCTIC 1x3 FP ATC, 55 gallon (200 litre) drum	495 lb (224 kg)	11.83 ft ³ (0.33 m ³)
20252	ARCTIC 1x3 FP ATC, 265 gallon (1000 litre) tote	2465 lb (1118 kg)	50.05 ft ³ (1.42 m ³)
20253	ARCTIC FP 1x3 ATC, bulk	Call Customer Services	



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:

www.Perimeter-Solutions.com

UNITED STATES

10667 Jersey Blvd.
Rancho Cucamonga, CA 91730

Tel: +1 800 682 3626
Tel: +1 909 983 0772

salesfoamusa@perimeter-solutions.com

EMEA

Polígono de Baiña, Parcela 23
33682 Mieres (Asturias)

Spain
Tel: +34 985 24 29 45

salesfoamea@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street
St Marys NSW 2760 – Australia

Tel: +61 2 9673 5300

salesfoamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.