

POLYFOAM 3/3U

AFFF—AR PSEUDOPLASTIC FOAM CONCENTRATE 3X3



DESCRIPTION

AFFF-AR compound for extinction of hydrocarbon and polar solvent fires. Concentrate with pseudoplastic behaviour. It contains fluorinated and hydrocarbon surfactants in order to allow the formation of an aqueous film on the surface of most hydrocarbon fuels, reducing vapour leaks and preventing the contact with the oxygen.

USE

It may be used with low expansion foam equipment (nozzles, monitors, foam chambers, etc.), non-aspirating devices (water spray nozzles and standard sprinklers) and medium expansion foam branches. On polar solvent fuels use gentle application.

DOSAGE

The dilution rate is 3% in fresh or sea water for extinguishing hydrocarbon fires and polar solvent (alcohols, ketones, ethers, esters, amines, etc) fires. It may be proportioned with standard equipment (in-line inductors, bladder tanks, balanced pressure systems, etc.) and special purpose ones for AFFF agents (e.g. Hydrofoam nozzles).



SPECIFICATIONS

The tables below show the **typical characteristics** of the concentrate and foam solutions.

CONCENTRATE	
Specific gravity @ 20°C	1.000-1.040
pH @ 20°C	7.0±0.5
Viscosity, cone and plate, 375/75 s-1 mPa.s	@ 20°C 80/265 @ +1.7°C 100/300
Freezing point, °C	< 0°
Lowest temperature for use, °C	+1.7°C (UL)

FOAM SOLUTION	
Dilution rate	3%
Surface tens. at 20°C, mN/m (Demineralised water)	17.0
Interfacial tens. with cyclohexane at 20°C, mN/m	1.5
Low Expansion Foam (UNI-86)	
Foam Expansion Index	>7.5
25% Drainage Time, min:s	>6:30

PERFORMANCE

The foam achieves a very quick knock-down of fires, even with low application rates, and shows an excellent burn-back resistance. The product has approval certifications according to **ICAO B, IMO (MSC.1/Circ.1312), EN 1568-3 (class IB) and EN 1568-4 (class IB/Acetone, class IA/IPA)**. The product is **UL Listed** with portable and fixed systems for hydrocarbons with type III application @ 0.10 gal/min-sq.ft and type II for alcohols @ 0.15 gal/min-sq.ft. Additionally, the PF-33U has approval certificate for **LASTFIRE** protocol with **GOOD** classification for all applications (semiaspirating, aspirating and system).

PACKAGING

The product is supplied in 20 or 25 L PE prismatic canisters, 200 L PE cylindrical drums and 1.000 L IBC containers.

STORAGE

The concentrate should be stored at temperatures between +17°C (UL requirement) and +50°C, preferably in the original containers or in stainless steel or epoxy lined tanks. Avoid permanent contact with carbon steel, iron, cooper alloys, aluminium, etc. Do not mix with other foam concentrates without a previous verification of compatibility.

⚠ CAUTIONS

Foams should not be used in contact with electrical equipment, neither with chemical products that can react with water. It is recommended to avoid the contact of the foam concentrate with the skin. In case of eye splashes, wash with plenty of water. In case of ingestion do not induce vomit, drink water and take medical advice.



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:
www.Perimeter-Solutions.com

UNITED STATES

1520 Brookfield Avenue
Green Bay, WI 54313
Tel: +1 (920) 593-9445
salesfoamusa@perimeter-solutions.com

EMEA

Polígono Industrial de Baiña, Parcela 23
33682 Baiña-Mieres (Asturias) – Spain
Tel: +34 985 24 29 45
salesfoamea@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street
St Marys NSW 2760 – Australia
Tel: +61 2 9673 5300
salesfoamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.