

H-930

SYNTHETIC MULTIEXPANSION FOAM CONCENTRATE (2%)



DESCRIPTION

Synthetic foam compound specially designed to be used in high and medium expansion foam gener-ators to fight class A and class B (hydrocarbon) fires. This product contains synthetic surfactants with a very good resistance to water hardness and it is easily biodegradable. The foam shows a good stability and drains slowly.

USE

Use with high, medium and low expansion foam equipment. High expansion foam with expansion coefficient of 500 to 1.000 is appropriate to extinguish indoor fires by suffocation. Medium expansion foam is a sufficient heavy foam to be used outdoors, filling small places, covering quickly spillages, etc. It can be used also to produce low and very-low (using wa-ter spray nozzles) expansion foam for general purposes (fighting A and B class fires); when it



is necessary to extinguish light hydrocarbon fires use gentle application and increase the application rate (I/min.m2) (note that in these cases an AFFF compound is more efficient).

DOSAGE

The proportioning rate is 2-3% in fresh or sea water for the production of all kind of foams.

SPECIFICATIONS

Typical characteristics of the concentrate and foam solutions are:

CONCENTRATE	
Specific gravity @ 20°C	1.06
pH @ 20°C	7.5-8
Viscosity, cone and plate, 375/75 s-1 mPa.s @ 20°C 0°C	20 50
Freezing point, °C	<-15
Lowest temperature for use, °C	-15

FOAM SOLUTION			
Dilution rate	2%		
Surface tens. at 20°C, mN/m (Demineralised water)	23.0		
Interfacial tens. with cyclohexane at 20°C, mN/m	3.0		
Low Expansion Foam (EN-1568-3)			
Foam Expansion Index	9.0		
25% Drainage Time, min:s	7:00		
Medium Expansion Foam (EN-1568-1)			
Foam Expansion Index	>125		
25% Drainage Time, min:s	>12:00		

SHIPPING

The product is supplied in 20 L PE prismatic containers or 200 L PE cylindrical drums or 1000L containers.

The H-930 has approval certification according to EN-1568-1 and EN-1568-3 with fresh and sea water (class IIIC). Below they are the results

STANDARD	EN-1568-3:2008		EN-1568-3:2008	
Fuel	Heptane		Heptane Heptane	
Application	-	-	Gentle	Gentle
Dilution rate, %	2	2	2	2
Water	Fresh	Salt	Fresh	Salt
Extinction	0:58	0:53	2:41	2:43
Burnback 25%, min:s	1%, 1:55	1%, 1:27	25%, 13:30	25%, 10:30
Classification	Pass	Pass	IIIC	IIIC

EN 1568:

EN 1568:

COMPATIBILITY

The H-930 concentrate does not show compatibility problems with other concentrates used in the same applications, and its foam can be applied simultaneously with others.

The foam concentrate shall be stored at temperatures between -15° and +50°C, preferably in their original containers, sealed. The product has no expiration date.

⚠ CAUTIONS

Foams should not be used in contact with electrical equipments, neither with chemical products that can react with water. It is recommended to avoid the contact of the foam concentrate with the skin. In case of eye splashes, wash with plenty of water. In case of ingestion do not induce vomit, drink water and take medical advice.



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:

www.Perimeter-Solutions.com

UNITED STATES

1520 Brookfield Avenue Green Bay, WI 54313 Tel: +1 (920) 593-9445 salesfoamusa@perimeter-solutions.com

EMEA

Polígono Industrial de Baiña, Parcela 23 33682 Baiña-Mieres (Asturias) - Spain Tel: +34 985 24 29 45 salesfoamemea@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street St Marys NSW 2760 - Australia Tel: +61 2 9673 5300 salesfoamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN