

# PHOS-CHEK® 1%

## FLUORINE FREE CLASS A/B FOAM CONCENTRATE



### DESCRIPTION

The first certified fluorine free **Class A/B firefighting foam, PHOS-CHEK® 1% fluorine free foam concentrate** is a mixture of water and hydrocarbon surfactants. Developed for use on Class B hydrocarbon fuel fires, this organohalogen free foam is an environmentally responsible next generation product, that demonstrates Perimeter Solutions' commitment to superior firefighting performance and environmental responsibility.

PHOS-CHEK 1% fluorine free foam is designed for rapid control and knockdown in both gentle and forceful applications on hydrocarbon fuel fires. PHOS-CHEK 1% fluorine free foam is an extremely effective wetting agent for use on Class A fires involving ordinary combustible materials such as wood, cloth, paper, rubber and many plastics.

### APPLICATIONS

PHOS-CHEK 1% fluorine free foam concentrate is designed for use on Class B hydrocarbon fuel fires (gasoline, crude oil, aviation fuels, diesel, etc.) at 1% proportioning. The foam concentrate is not intended for use on Class B polar solvents or water miscible fuels such as alcohols, ketones, esters and others. On Class A fuels, the foam concentrate is used as a wetting agent in accordance with ANSI/NFPA 18.

PHOS-CHEK 1% fluorine free foam concentrate is compatible with conventional firefighting equipment such as low expansion non-air aspirating and air aspirating nozzles and monitors, medium expansion foam devices and Compressed Air Foam Systems (CAFS).

### PRODUCT CERTIFICATIONS

UL 162/ULC S654 Listed, UL/ULC Classified Class A Wetting Agent ANSI/NFPA 18, EN-1568-3:2008 (Class 1B) Approved, EN-1568-3:2018 (Class 1B) Approved, EN1568-3:2018 at 3% on Diesel (Class 1+A) Approved, LASTFIRE Batch Tested.



### TYPICAL PHYSICAL PROPERTIES

<b>Specific Gravity @ 68 °F (20 °C)</b>	<b>1.020 – 1.060</b>
<b>pH</b>	<b>87.0 ± 0.5</b>
<b>Viscosity (LV-1 Spindle @ 60 RPM)*</b>	<b>2 – 10 cP</b>
<b>Refractive Index</b>	<b>1.3700 – 1.3800</b>
<b>Lowest Temperature for Use</b>	<b>35 °F (-1.7 °C)</b>
<b>Freezing Point</b>	<b>23 °F (-5 °C)</b>

\*Brookfield LVT

### WETTING AGENT APPLICATION RATES

UL/ULC Classified 0.1% for Class A fires and 0.25% for Class B Non-Water Miscible Fires

- Class A fire use, mix 0.1 part foam concentrate to 99.9 parts water.
- Class B fire use, mix 0.25 part foam concentrate to 99.75 parts water.

### SHELF LIFE, INSPECTION AND TESTING

The shelf life of any foam concentrate is maximized by proper storage conditions and maintenance. Factors affecting shelf life are wide temperature fluctuation, evaporation, dilution, and contamination by foreign materials. Properly stored PHOS-CHEK 1% fluorine free foam concentrates should have no significant loss of fire fighting performance for 20+ years. However, the National Fire Protection Association (NFPA) recommends annual testing of all firefighting foams.

**HANDLING PRECAUTIONS**

- For DETAILED SAFETY INFORMATION, please refer to the SDS.
- **Precautionary Measures:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary contact and removal of the material from the eyes, skin and clothing.
- **Eye Protection:** As a good industrial practice, the use of chemical goggles is recommended.
- **If in the eyes:** Flush with plenty of water.
- **Skin Protection:** Wear protective gloves when handling concentrate to minimize skin contact. Wash hands and contaminated skin after handling.
- **Respiratory Protection:** None required.
- For complete SDS, visit [perimeter-solutions.com](http://perimeter-solutions.com)



**STORAGE AND HANDLING**

The concentrate should be stored at temperatures between 35 °F (1.7 °C)\*\* and 120 °F (49 °C), preferably in the original containers, approved bladder tanks, stainless steel, high density polyethylene, fiberglass or epoxy lined tanks. Concentrate piping acceptable materials of construction include stainless steel (either 304 or 316), some plastic piping including fiber glass and PVC, red brass, and black iron as long as the system is completely flooded eliminating the air/foam concentrate/carbon steel interface. Avoid permanent contact with carbon steel, iron, some copper alloys, & aluminum when the piping material and concentrate will be exposed to air. Galvanized piping should not be used in direct contact with the foam concentrate.

Foam concentrates are subject to evaporation, which accelerates when the product is exposed to air. Storage tanks should be sealed and fitted with a pressure vacuum vent to prevent free exchange of air.

**ENVIRONMENTAL INFORMATION**

PHOS-CHEK foam concentrates do not contain intentionally added PFAS chemicals including PFOA and PFOS. In making this statement, Perimeter Solutions relies on information provided by its raw material suppliers and certain independent laboratory analysis conducted on the product.

**PACKAGING**

**ORDERING INFORMATION**

PHOS-CHEK 1% FLUORINE FREE	lb*	kg*	Part #
<b>5 Gallon Pail (20 litres)</b>	<b>43</b>	<b>19</b>	<b>10004067</b>
<b>55 Gallon Drum (200 litres)</b>	<b>468</b>	<b>212</b>	<b>10004066</b>
<b>265 Gallon Tote (1,000 litres)</b>	<b>2255</b>	<b>1023</b>	<b>10004067</b>

\*Approximate shipping weight

Contact your local authorized PHOS-CHEK distributor or factory sales representative for additional details. [perimeter-solutions.com](http://perimeter-solutions.com)

\*\*EN APPROVAL at 35 °F (1.7 °C) and 122 °F (50 °C)



**Solutions That Save.**

**FOR MORE INFORMATION**

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit: [www.perimeter-solutions.com](http://www.perimeter-solutions.com)

**UNITED STATES**

10667 Jersey Blvd.  
Rancho Cucamonga, CA 91730  
Tel: +1 800 682 3626  
Tel: +1 909 983 0772  
[salesfoamusa@perimeter-solutions.com](mailto:salesfoamusa@perimeter-solutions.com)

**EMEA**

Polígono Industrial de Baiña, Parcela 23  
33682 Baiña-Mieres (Asturias) – Spain  
Tel: +34 985 24 29 45  
[salesfoamemea@perimeter-solutions.com](mailto:salesfoamemea@perimeter-solutions.com)

**ASIA PACIFIC**

3 Charles Street  
St Marys NSW 0276 – Australia  
Tel: +61 2 9673 5300  
[salesfoamapac@perimeter-solutions.com](mailto:salesfoamapac@perimeter-solutions.com)

[perimeter-solutions.com](http://perimeter-solutions.com)

**NOTICE** PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.