

PHOS-CHEK® 3% MS

AFFF MIL-SPEC AQUEOUS FILM FORMING FOAM CONCENTRATE



DESCRIPTION

PHOS-CHEK® 3% AFFF MIL-SPEC film forming foam concentrate was the first all C6 based product on the Department of Defense Qualified Product Database (QPD) – Qualified Products List (QPL). In 2016, PHOS-CHEK 3% AFFF MIL-SPEC was selected by the US Air Force as the product of choice on all of their Aircraft Rescue Firefighting trucks globally. The MIL-SPEC testing protocol is the most rigorous test program for foam concentrates. The foams must pass multiple fire tests and confirm performance when diluted with both fresh and sea water. Fire performance is confirmed in both 2.6m² and 4.6m² unleaded gasoline pool fires at half strength and five times concentration. Other requirements include chemical and physical property specifications, foam quality (expansion and drain time), film formation, and sealability tests. The MIL-SPEC test protocol also includes extensive environmental impact based on biodegradability studies like Biological Oxygen Demand (BOD), Chemical Oxygen Demand (COD), and aquatic toxicity.



APPLICATIONS

PHOS-CHEK 3% AFFF MIL-SPEC may be used with low expansion foam equipment (nozzles and monitors), non-aspirating devices (water spray nozzles and standard sprinklers) and medium expansion foam devices to fight fires involving Class B hydrocarbon fuel fires such as aviation fuels, hydraulic oil, and diesel fuels. It is not suitable for use on polar solvents or water miscible fuels such as alcohols, ketones, esters, and ethers.

APPROVAL CERTIFICATIONS

DOD Spec MIL-PRF-24385 QPD Approved, UL 162 Listed.

TYPICAL PHYSICAL PROPERTIES

Specific gravity @ 68 °F (20 °C)	1.002 – 1.042
pH	8.1 ± 0.5
Viscosity (LV-1 Spindle @ 60 RPM)*	2 – 10 cP
Refractive Index	1.3650 – 1.3750
Lowest Temperature for Use	35 °F (1.7 °C)
Freezing Point	24.8 °F (-4 °C)

*Brookfield LVT

SHELF LIFE, INSPECTION AND TESTING

The shelf life of any foam concentrate is maximized by proper storage conditions and maintenance. Factors affecting shelf life are wide temperature fluctuation, evaporation, dilution, and contamination by foreign materials. Properly stored PHOS-CHEK AFFF Class B foam concentrates should have no significant loss of firefighting performance for 20+ years. However, the National Fire Protection Association (NFPA) recommends annual testing of all firefighting foams.

STORAGE AND HANDLING

The concentrate should be stored at temperatures between 35 °F (1.7 °C) and 120 °F (49 °C), preferably in the original containers, approved bladder tanks, stainless steel, high density polyethylene, fiberglass or epoxy lined tanks. Concentrate piping acceptable materials of construction include stainless steel (either 304 or 316), some plastic piping including fiberglass and PVC, red brass, and black iron as long as the system is completely flooded eliminating the air/foam concentrate/carbon steel interface. Avoid permanent contact with carbon steel, iron, some copper alloys, & aluminum when the piping material and concentrate will be exposed to air. Galvanized piping should not be used in direct contact with the foam concentrate.

Foam concentrates are subject to evaporation, which accelerates when the product is exposed to air. Storage tanks should be sealed and fitted with a pressure vacuum vent to prevent free exchange of air.



HANDLING PRECAUTIONS

- For DETAILED SAFETY INFORMATION, please refer to the SDS.
- **Precautionary Measures:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary contact and removal of the material from the eyes, skin and clothing.
- **Eye Protection:** As a good industrial practice, the use of chemical goggles is recommended.
- **If in the eyes:** Flush with plenty of water.
- **Skin Protection:** Wear protective gloves when handling concentrate to minimize skin contact. Wash hands and contaminated skin after handling.
- **Respiratory Protection:** None required.
- For complete SDS, visit perimeter-solutions.com

PACKAGING

ORDERING INFORMATION			
PHOS-CHEK 3% AFFF MIL-SPEC	lb.*	kg.*	Part #
5 gallon pail (20 litres), PHOS-CHEK 3% AFFF MIL-SPEC NSN 4210-01-668-6235	43	19	10004164
55 gallon drum (200 litres), PHOS-CHEK 3% AFFF MIL-SPEC NSN 4210-01-668-6228	468	212	10004112
265 gallon tote (1,000 litres), PHOS-CHEK 3% AFFF MIL-SPEC	2255	1023	10004192

*Approximate shipping weight

Contact your local authorized PHOS-CHEK distributor or factory sales representative for additional details. perimeter-solutions.com



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:
www.Perimeter-Solutions.com

UNITED STATES

1520 Brookfield Avenue
Green Bay, WI 54313
Tel: +1 800 682 3626
Tel: +1 920 593 9445
salesfoamusa@perimeter-solutions.com

EMEA

Polígono de Baiña, Parcela 23
33682 Mieres (Asturias)
Spain
Tel: +34 985 24 29 45
salesfoamema@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street
St Marys NSW 2760 – Australia
Tel: +61 2 9673 5300
salesfoamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.