

# PHOS-CHEK® FIRST RESPONSE

## CLASS A FOAM CONCENTRATE



### DESCRIPTION

**PHOS-CHEK® FIRST RESPONSE** foam concentrate is specially formulated to make water more effective for fire fighting. PHOS-CHEK FIRST RESPONSE is a budget conscious Class A foam concentrate that compares favorably with other less concentrated Class A foam products.

The unique combination of surfactants significantly reduces water's surface tension and, when mixed with air, creates a foam blanket that surrounds fuels with a thick layer of water. This creates a barrier between the fuel and the fire, knocking down the fire faster than water alone, and allows fire fighters to see the areas of application. Making the water more effective reduces the amount of water needed to extinguish the fire reducing water damage and increases fire fighter safety through quicker knockdown and reduced mop-up/overhaul requirements. PHOS-CHEK FIRST RESPONSE contains NO HAZARDOUS MATERIALS, is non corrosive, non-toxic, readily biodegradable, and has no flash point.

PHOS-CHEK FIRST RESPONSE Class A foam concentrate does not contain PFAS chemicals including, but not limited to, PFOS or PFOA. Fluorinated surfactants are used in Class B foam concentrates and are necessary to form a film on flammable liquid fires. Class B foams should not be used on Class A fires. Never mix Class A and Class B foam concentrates.

### QUALIFICATIONS AND USES

PHOS-CHEK FIRST RESPONSE is fully tested and qualified for use by the USDA Forest Service under Specification 5100-307b for all application methods including ground engines,



### PRODUCT CHARACTERISTICS

<b>Color/Odor</b>	<b>Tan liquid with a hint of orange blossom</b>
<b>Viscosity</b>	<b>&lt;50 centipoise (cP) at 70 oF (21 °C)</b>
<b>Density</b>	<b>8.43-8.6 lbs/US gallon, 1.01-1.03 kg/liter</b>
<b>pH</b>	<b>6.75-8.25</b>
<b>Surface Tension</b>	<b>34.6 dynes/cm2 @ 0.3%</b>

Canadair water scooper aircraft, single engine air tankers (SEATS), and fixed tank helicopters. PHOS-CHEK FIRST RESPONSE is compatible with fresh water, sea-water and long-term retardant. Foam characteristics are not affected by freeze-thaw.

PHOS-CHEK FIRST RESPONSE meets the requirements of NFPA 1150. It is effective for use in Compressed Air Foam Systems (CAFS).

### USE RATES

- Wetting Agent: 0.2%
- Direct attack: 0.6% to 1.0%
- Mop Up/Overhaul: 0.2% to 0.6%.

### APPLICATIONS

	LONG-TERM RETARDANT	GEL	CLASS A FOAM	WATER
<b>Indirect Attack</b>	✓✓✓✓	✓✓	✓	
<b>Direct/Parallel Attack</b>	✓✓✓✓	✓✓✓	✓✓	✓
<b>Interior Structure Attack</b>		✓✓	✓✓✓✓	✓
<b>Structure Protection: -Indirect Application</b>	✓✓✓✓	✓✓✓	✓✓	✓
<b>Structure Protection: -Direct Application</b>		✓✓✓✓	✓✓✓	✓
<b>Mop Up</b>	✓✓	✓✓	✓✓✓✓	✓
<b>Prescribed Burn Control</b>	✓✓✓✓	✓✓✓	✓✓	✓

- ✓✓✓✓ = Superior Effectiveness
- ✓✓✓ = Excellent Effectiveness
- ✓✓ = Good Effectiveness
- ✓ = Baseline Effectiveness

**HANDLING PRECAUTIONS**

- **For detailed safety information, please refer to the SDS.**
- PHOS-CHEK FIRST RESPONSE concentrate is moderately irritating to eyes and slightly irritating to skin. Prolonged or repeated contact with the concentrate may produce skin irritation and inhalation of its mists may irritate the nose and upper respiratory system.
- **Eye Protection:** Goggles are recommended when handling concentrate. If in the eyes, flush immediately with plenty of water for at least 15 minutes.
- **Skin Protection:** Wear protective clothing and chemical resistant gloves when handling concentrate. Exposed skin should be washed as soon as possible.
- **Respiratory Protection:** None required. Avoid breathing mist or vapor.
- **Other Precautions:** Keep container closed. Use with adequate ventilation.
- These precautions and practices are similar to those used with any heavy-duty detergent.
- Water solutions of PHOS-CHEK FIRST RESPONSE at use levels (0.1%-1.0%) are only minimally irritating, but should be washed from the skin as soon as practical, as drying and chapping could result from prolonged exposure.
- For complete SDS, visit [www.perimeter-solutions.com](http://www.perimeter-solutions.com)

**ENVIRONMENTAL INFORMATION**

PHOS-CHEK FIRST RESPONSE Class A foam concentrate does not contain PFAS chemicals commonly found in fluorinated Class B foam concentrates. Perimeter Solutions foam manufacturing process is intentionally separated between fluorinated and non-fluorinated concentrate types, thus eliminating the potential for cross contamination or residual contamination.

**PACKAGING**

ORDERING INFORMATION			
PHOS-CHEK FIRST RESPONSE	lbs*	kgs*	Part #
<b>5 Gallon Pail (19 litres)</b>	<b>45</b>	<b>19</b>	<b>10001316</b>
<b>55 Gallon Drum (205 litres)</b>	<b>470</b>	<b>212</b>	<b>10001347</b>
<b>260 Gallon Tote (985 litres)</b>	<b>2255</b>	<b>1023</b>	<b>10000857</b>

\*Approximate shipping weight

\*Contact your local authorized PHOS-CHEK distributor or factory sales representative for additional details. <https://www.perimeter-solutions.com>



**Solutions That Save.**

**FOR MORE INFORMATION**

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit: [www.Perimeter-Solutions.com](http://www.Perimeter-Solutions.com)

**UNITED STATES**

10667 Jersey Blvd.  
Rancho Cucamonga, CA 91730  
Tel: +1 800 682 3626  
Tel: +1 909 983 0772  
[salesfoamusa@perimeter-solutions.com](mailto:salesfoamusa@perimeter-solutions.com)

**EMEA**

Polígono Industrial de Baiña, Parcela 23  
33682 Baiña-Mieres (Asturias) – Spain  
Tel: +34 985 24 29 45  
[salesfoamemea@perimeter-solutions.com](mailto:salesfoamemea@perimeter-solutions.com)

**ASIA PACIFIC**

3 Charles Street  
St Marys NSW 2760 – Australia  
Tel: +61 2 9673 5300  
[salesfoamapac@perimeter-solutions.com](mailto:salesfoamapac@perimeter-solutions.com)

[perimeter-solutions.com](http://perimeter-solutions.com)

**NOTICE** PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.