

SOLBERG® FIRE-BRAKE 3150A FOAM CONCENTRATE



TYPICAL PHYSICAL PROPERTIES AT 77 °F (25 °C)

Appearance: Clear, light yellow liquid
Freezing Point: 27°F (-3°C)
 (No quality loss after thawing)
Maximum Storage Temp: 120°F
 (49°C)
pH: 7.0 - 8.5
Refractive Index: 1.3555 - 1.3595
Specific Gravity: 1.000 - 1.040
Viscosity: 3.0 - 5.0 cSt*
Sediments: < 0.05%
 *Cannon - Fenske Viscometer



APPLICATION

SOLBERG Fire-Brake 3150A Class A foam concentrate is designed and applied to Class A fires including wood, paper, coal, rubber, wildland and structure fires. SOLBERG Fire-Brake 3150A Class A foam concentrate is compatible with conventional firefighting equipment such as non-air aspirating and air aspirating foam nozzles, Compressed Air Foam Systems (CAFS), rotary and fixed wing aircraft, low, medium and high expansion devices and has an admixture rate of 0.1% to 1.0% depending on use. Fire-Brake 3150A should not be mixed with other foam concentrates.

APPLICATION RATES

Recommended application rates—
SOLBERG Fire-Brake 3150A Class A foam concentrate:

Mop-up: 0.25%

Suited for mop-up/overhaul, quickly penetrates Class A substrates

Initial Suppression: 0.5%

Penetrates tree canopies, draining to the forest floor layers and direct attack for structural firefighting

Fire-Brake 3150A: 0.75%

Good for initial suppression or forming a barrier

Protection: 1.0%

Adheres and insulates vertical surfaces

The minimum admixture rate on other Class A fuel types is 0.1%.

DESCRIPTION

SOLBERG® Fire-Brake 3150A CLASS A FOAM CONCENTRATE from SOLBERG is a synthetic firefighting foam concentrate specially designed to be used for wildland, structural and other Class A fuel fires. SOLBERG Fire-Brake 3150A Class A foam concentrate has the ability to reduce the surface tension of water, which substantially increases water's overall wetting capability. This creates a faster penetration and greater fire control when attacking combustible Class A fuels. SOLBERG Fire-Brake 3150A Class A foam concentrate can be proportioned at the rate of 0.1 - 1% in fresh, sea and brackish water.

PERFORMANCE

Fire Performance

SOLBERG Fire-Brake 3150A Class A foam concentrate has been tested to and meets the performance requirements of the U.S. Forest Service, Qualified Products List, Specification 5100-307a (as amended) for the applications as determined during the product evaluation and shown on the QPL, and meets the requirements of National Fire Protection Association (NFPA) 1150—Standard on Foam Chemicals for Fires in Class A Fuels (current edition).

Foam Proportioning

SOLBERG Fire-Brake 3150A Class A foam concentrate can be proportioned using most proportioning equipment:

- Balanced pressure pump systems
- Bladder tank systems
- CAFS
- Eductors (with metering orifice)

STORAGE

The storage temperature range for SOLBERG Fire-Brake 3150A Class A foam concentrate is 27°F to 120°F (-3°C to 49°C).

When stored in original containers or in manufacturer recommended equipment and within the specified temperature range, the shelf life is 10 years or more.

SOLBERG® FIRE-BRAKE 3150A CLASS A FOAM CONCENTRATE

COMPATIBILITY

SOLBERG Fire-Brake 3150A Class A foam concentrate should not be mixed with other foam concentrates. However, when the foam solution is applied to a fire the product can be mixed with other similar foam types. For questions about compatibility or mixing, consult Perimeter Solutions Technical Services.

Materials of Construction Capability

SOLBERG Fire-Brake 3150A Class A foam concentrate is compatible with multiple materials of construction such as carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate. For questions about material compatibility, consult Perimeter Solutions Technical Services.

ENVIRONMENTAL INFORMATION

SOLBERG Fire-Brake 3150A is biodegradable. When used and disposed of properly, this product does not adversely affect aquatic life. SOLBERG Fire-Brake 3150A Class A foam concentrate does not contain any PFAS ingredients commonly found in fluorinated Class B foam concentrates. Perimeter Solutions foam manufacturing process is intentionally separated between fluorinated and non-fluorinated concentrate types, thus eliminating the potential for cross contamination or residual contamination.

CERTIFICATIONS

SOLBERG Fire-Brake 3150A Class A foam concentrate is Qualified Products Listed (QPL) by the U.S. Forest Service in accordance with Forest Service Specification 5100-307a.

ORDERING INFORMATION

SOLBERG Fire-Brake 3150A Class A foam concentrate is available in pails, drums, totes and bulk quantities.

Part No.	Description	Approximate Shipping Weight	Approximate Cube
AUFB20L-20001	SOLBERG Fire-Brake 3150A Class A foam concentrate, 20 Litre Pail	45 lb (21 kg)	1.25 ft ³ (0.04 m ³)
AUFB200L-20002	SOLBERG Fire-Brake 3150A Class A foam concentrate, 200 Litre Drum	495 lb (224 kg)	11.83 ft ³ (0.33 m ³)
AUFB1000L-20003	SOLBERG Fire-Brake 3150A Class A foam concentrate, 1000 Litre IBC	2465 lb (1118 kg)	50.05 ft ³ (1.42 m ³)



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:
www.Perimeter-Solutions.com

UNITED STATES

10667 Jersey Blvd.
Rancho Cucamonga, CA 91730
Tel: +1 800 682 3626
Tel: +1 909 983 0772
salesfoamusa@perimeter-solutions.com

EMEA

Polígono de Baiña, Parcela 23
33682 Mieres (Asturias)
Spain
Tel: +34 985 24 29 45
salesfoamemea@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street
St Marys NSW 2760 – Australia
Tel: +61 2 9673 5300
salesfoamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.