

PHOS-CHEK® FLASH 21

FUEL GELLING AGENT



DESCRIPTION

Ground and Heli-torches require gelled fuel. PHOS-CHEK FLASH 21 is a two-part liquid fuel gelling agent that reliably provides high quality gel, fast. Fuel thickened with PHOS-CHEK FLASH 21 achieves ideal viscosity with no settling. FLASH 21 can be mixed with various fuels including straight gasoline, diesel, Jet A or Jet B if available. Using Jet A alone will produce a good gel but because of the low flash point of this type of fuel, you may need to add 20-30% straight gas to produce a better ignition point.

PHOS-CHEK FLASH 21 was developed to allow mixing with fuel regardless of temperature, ensuring a consistent gelled fuel mixture. Fuel treated with FLASH 21 will not lose viscosity, allowing use during an entire burning operation. For additional information on safety and handling, please refer to the product labels and Safety Data Sheets which are available for both products.

FLASH 21 is designed to be added to fuel as two parts, A and B, one liter of each component part. One carton of FLASH 21 has 12 liters of product, six of FLASH 21A and six of FLASH 21B. One liter of Part A and one liter of Part B will gel 55 U.S. gallons (208 litres) of fuel. Freezing does not adversely affect either Part A or B; once the product thaws it can effectively be used. Under cold weather conditions it is recommended that a 10-25% blend of regular gasoline is used when mixing Jet A, Jet B or diesel fuel. High temperature has no impact on any of the standard fuels.



ADVANTAGES OF PHOS-CHEK FLASH 21

- Ease of mixing and superior long-term viscosity stability makes FLASH 21 the preferred gelling agent in today's market.
- No noticeable effects from either cold or warm temperatures provide burn specialists a maximum window of operations.
- FLASH 21 provides the user with a high consistent fuel gel mixture; it eliminates the problems of product lumping and viscosity loss commonly experienced with other available products. FLASH 21 is effective with fuels containing ethanol.

MIXING INSTRUCTIONS USING ETHANOL FUELS

When using PHOS-CHEK FLASH 21 in conjunction with ethanol blended fuels, it is essential that the user be aware that ethanol will inhibit the gelling process. This can be overcome by following the simple steps outlined below:

1. Determine the amount of Ethanol Blended Fuel (EBF) present in the volume of fuel to be gelled, i.e. a normal 200 litre drum of fuel containing a blend of 50% diesel mixed with 50% EBF would contain 100 litres of ethanol blended fuel.
2. Take a volume of water equal to 5% of the volume of EBF present in the mix (5% of 100 liters = 5 liters of water required) and add it to the fuel volume to be gelled.
3. Add the FLASH 21A component and stir for approximately 1 minute. Then add the FLASH 21B component and continue to stir the blend. Gelling should take place in less than 5 minutes. The ethanol present in ethanol/gasoline blends sets up a chemical barrier between the FLASH 21 components in the mixture, and the hydrocarbon fuels that it must act upon to create the gelled fuel. The water, when added to the fuel blend, serves to "tie" the ethanol component, which then allows the FLASH 21 to access the hydrocarbon molecules, and gelling action can take place. The "tied" blend of water and ethanol will begin to percolate through the gelled fuel and will collect at the bottom of the mixture as a thin, brownish liquid. This process will begin quickly and should normally be completed in less than 12 hours. If gel from an EBF mixture has been left for any length of time prior to commencing operations, this brownish liquid can be readily mixed back into the gel structure by simply stirring the gel, rolling the barrel if practical, etc. No reports of impaired ignition have been noted and burning should proceed as normal.



The gel produced using EBF tends to be thinner than gels produced using non-EBF types. If EBF use is necessary, but a thicker gel is needed, consider the option below:

BLENDING THE EBF WITH A HIGHER CARBON FUEL, SUCH AS DIESEL: Gel produced by ethanol blended fuel may exhibit a lower blending in a higher carbon fuel such as diesel to achieve a thicker gel.

EQUIPMENT CLEANLINESS: Prior to use, it is essential to flush the equipment with raw fuel to remove contaminants from all plumbing and surfaces before mixing with FLASH 21. Residual amounts of other gelling agents may negatively affect the ability of FLASH 21 to work as intended, even in minute quantities.

ORDERING INFORMATION

FLASH 21A and FLASH 21B are packaged in one-litre (33.8 Oz.) Plastic bottles. There are 6 bottles of each component in a case. Each case weights 16 kg. (35 Lbs.)

PACKAGING

ORDERING INFORMATION			
	lb.*	kg.*	Part #
Case, Two-part Fuel Gelling Agent – FLASH 21 [contains six 1 litre (34 oz.) containers FLASH 21A and six 1 litre (34 oz.) containers FLASH 21B]	31	14	10002236
Case, IATA Approved – Aircraft Shipment, Two-part Fuel Gelling Agent – FLASH 21 [contains two 1 litre (34 oz.) containers FLASH 21A and two 1 litre (34 oz.) containers FLASH 21B]	11	5	10002592

*Approximate shipping weight

*Contact your local authorized PHOS-CHEK distributor or factory sales representative for details perimeter-solutions.com



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:

www.Perimeter-Solutions.com

UNITED STATES

1520 Brookfield Avenue
Green Bay, WI 54313

Tel: +1 (920) 593-9445

salesfoamusa@perimeter-solutions.com

EMEA

Polígono Industrial de Baiña, Parcela 23
33682 Baiña-Mieres (Asturias) – Spain

Tel: +34 985 24 29 45

salesfoamemea@perimeter-solutions.com

ASIA PACIFIC

46 Hudson Crescent
Lavington NSW 2641 - Australia

Tel: +61 2 6040 6900

PC.SalesAPAC@perimeter-solutions.com

CANADA

3060 Airport Road
Kamloops, BC V2B 7X2

Tel: +1 250 554 3530

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.