

SOLBERG SPARTAN™ 1%

FLUORINE-FREE CLASS A/B FOAM CONCENTRATE



FAST FACTS

- One foam for multiple fuels – Independently approved on Class A and Class B fuels
- UL 162 listed at 1% for Class B Hydrocarbon fuel fire
- UL Wetting Agent – listed for both Class A and Class B fires
- Low viscosity (water like), easy to proportion and use with conventional firefighting equipment
- Designed to give firefighters a tactical advantage to achieve total fire suppression on structure, wildland, vehicle, gasoline, and dumpster fires
- Dramatically cuts water usage



APPLICATIONS

SOLBERG SPARTAN 1% fluorine-free foam concentrate is designed for use on Class A and Class B hydrocarbon fuel fires (gasoline, crude oil, aviation fuels, diesel, etc.) at 1% proportioning. The foam concentrate is not intended for use on Class B polar solvents or water miscible fuels, such as alcohols, ketones, esters and others. On Class A fuels, the foam concentrate is used as a wetting agent in accordance with ANSI/NFPA 18.

SOLBERG SPARTAN 1% is compatible with conventional firefighting equipment, such as inline edcutors, self-inducting nozzles, low-expansion non-air aspirating and air aspirating nozzles, monitors, medium-expansion foam devices and Compressed Air Foam Systems (CAFS). With similar viscosity to Class A foam, SOLBERG SPARTAN is also compatible with onboard proportioning systems.

DESCRIPTION

SOLBERG SPARTAN™ 1% is our most effective fluorine-free Class A/B foam concentrate. This world-leading technology is designed to provide firefighters with a tactical advantage to achieve total fire suppression on structure, wildland, vehicle, gasoline, and dumpster fires.

One foam, 99% of fires. Providing cooling and fire suppression power, SOLBERG SPARTAN 1% knocks down flames fast, reduces flashover conditions, and shields structures from heat and flame. It delivers fast fire knockdowns, efficiency, and great resource utilization. Its fast extinguishment reduces water usage and property damage.

SOLBERG SPARTAN 1% has low viscosity and is easy to proportion. Engineered for rapid knockdown, it extends tactical endurance and reduces strain on critical resources -- allowing crews to operate more efficiently.

CERTIFICATIONS

- **UL 162/ULC S654 Listed - 1% for Class B** Hydrocarbon Non Water Miscible Fuel Fires
- **UL/ULC Classified** - 0.1% for Class A fires and 0.25% for Class B Non-Water Miscible Fires
- **Class A Wetting Agent** in accordance with ANSI/NFPA 18

TYPICAL PHYSICAL PROPERTIES

Specific Gravity @ 68 °F (20 °C)	1.020 – 1.060
pH	7.0 ± 0.5
Viscosity (LV-1 Spindle @ 60 RPM)*	2 – 10 cP
Refractive Index	1.3700 – 1.3800
Lowest Temperature for Use	35 °F (1.7 °C)
Freezing Point	23 °F (-5 °C)

*Brookfield LVT

INSPECTION

SOLBERG SPARTAN 1%, or a premix solution, should be tested annually per National Fire protection Association (NFPA 11). A sample of the foam concentrate should be sent to the manufacturer or qualified third-party lab to confirm physical properties and foam quality meet the specifications of the foam as originally supplied as per the requirements of NFPA 11.

PACKAGING

ORDERING INFORMATION			
SOLBERG SPARTAN 1% FLUORINE-FREE	lbs.*	kgs.*	Part #
5 Gallon Pail (19 litres)	43	19	20962
55 Gallon Drum (208 litres)	468	212	20963
265 Gallon Tote (1003 litres)	2255	1023	20964

*Approximate shipping weight

Contact your local authorized SOLBERG distributor or factory sales representative for additional details. perimeter-solutions.com

⚠ CAUTIONS

Foams should not be used in contact with electrical equipment or with chemical products that can react with water. It is recommended to avoid contact of the foam concentrate with skin. In case of eye splashes, wash with plenty of water. In case of ingestion do not induce vomiting, drink water and seek medical advice.

Contains no intentionally added PFAS.

STORAGE/MATERIAL COMPATIBILITY

SOLBERG SPARTAN 1% should be stored between 0 °C and +50 °C, preferably in the original containers. It is compatible with multiple materials of construction found in firefighting equipment. For questions about material of construction compatibility, consult Perimeter Solutions technical services.

The shelf life of any foam concentrate is maximized by proper storage conditions and maintenance. Factors affecting shelf life are wide temperature fluctuation, evaporation, dilution, and contamination by foreign materials. When stored in original containers or in manufacturer-recommended equipment and within the specified temperature range, SOLBERG foam concentrates have demonstrated effective firefighting performance for 10 years or greater.

SOLBERG-manufactured products are thoroughly inspected and undergo rigorous quality control tests. These evaluations analyze the foam's physical parameters as well as the finished product's fire performance. A Certificate of Analysis (CoA) is issued with every batch.



Trusted. Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:
www.Perimeter-Solutions.com

UNITED STATES

1520 Brookfield Avenue
Green Bay, WI 54313
Tel: +1 800 682 3626
Tel: +1 920 593 9445
salesfoamusa@perimeter-solutions.com



NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.