

SOLBERG® FIRE-BRAKE PLUS™

CLASS A FOAM CONCENTRATE



DESCRIPTION

SOLBERG® FIRE-BRAKE PLUS™ foam concentrate is specially formulated to make water more effective for fire fighting. SOLBERG FIRE-BRAKE PLUS is a budget conscious Class A foam concentrate that compares favorably with other less concentrated Class A foam products.

The unique combination of surfactants significantly reduces water's surface tension and, when mixed with air, creates a foam blanket that surrounds fuels with a thick layer of water. This creates a barrier between the fuel and the fire, knocking down the fire faster than water alone, and allows fire fighters to see the areas of application. Making the water more effective reduces the amount of water needed to extinguish the fire reducing water damage and increases fire fighter safety through quicker knockdown and reduced mopup/overhaul requirements. SOLBERG FIRE-BRAKE PLUS contains NO HAZARDOUS MATERIALS, is non corrosive, non-toxic, readily biodegradable, and has no flash point.

SOLBERG FIRE-BRAKE PLUS Class A foam concentrate does not contain PFAS chemicals including, but not limited to, PFOS or PFOA. Fluorinated surfactants are used in Class B foam concentrates and are necessary to form a film on flammable liquid fires. Class B foams should not be used on Class A fires. Never mix Class A and Class B foam concentrates.

QUALIFICATIONS AND USES

SOLBERG FIRE-BRAKE PLUS is fully tested and qualified for use by the USDA Forest Service under Specification 5100-307b for all application methods including ground engines, Canadair water scooper aircraft, single engine air tankers (SEATS), and fixed tank helicopters. SOLBERG FIRE-BRAKE PLUS is compatible with fresh water, sea-water and long-term retardant. Foam characteristics are not affected by freeze-thaw.

SOLBERG FIRE-BRAKE PLUS meets the requirements of NFPA 1150. It is effective for use in Compressed Air Foam Systems (CAFS).



PRODUCT CHARACTERISTICS

Color/Odor	Tan liquid with a hint of orange blossom
Viscosity	<50 centipoise (cP) at 70 oF (21 °C)
Density	8.43-8.6 lbs/US gallon, 1.01-1.03 kg/liter
pH	6.75-8.25
Surface Tension	34.6 dynes/cm2 @ 0.3%

USE RATES

- · Wetting Agent: 0.1 0.2%
- · Direct attack: 0.6% to 1.0%
- · Mop Up/Overhaul: 0.2% to 0.6%
- · Back Burn: 0.75%

APPLICATIONS

	LONG-TERM RETARDANT	GEL	CLASS A FOAM	WATER
Indirect Attack	***	4 4	•	
Direct/Parallel Attack	***	444	* *	~
Interior Structure Attack		4 4	***	✓
Structure Protection: -Indirect Application	~ ~ ~ ~	444	* *	*
Structure Protection: -Direct Application		***	* * *	~
Мор Up	4 4	4 4	**	✓
Prescribed Burn Control	***	**	* *	✓



HANDLING PRECAUTIONS

- For detailed safety information, please refer to the SDS.
- SOLBERG FIRE-BRAKE PLUS
 concentrate is moderately irritating
 to eyes and slightly irritating to skin.
 Prolonged or repeated contact with the
 concentrate may produce skin irritation
 and inhalation of its mists may irritate
 the nose and upper respiratory system.
- Eye Protection: Goggles are recommended when handling concentrate. If in the eyes, flush immediately with plenty of water for at least 15 minutes.
- Skin Protection: Wear protective clothing and chemical resistant gloves when handling concentrate. Exposed skin should be washed as soon as possible.
- Respiratory Protection: None required.
 Avoid breathing mist or vapor.
- Other Precautions: Keep container closed. Use with adequate ventilation.
- These precautions and practices are similar to those used with any heavyduty detergent.
- Water solutions of SOLBERG FIRE-BRAKE PLUS at use levels (0.1%-1.0%) are only minimally irritating, but should be washed from the skin as soon as practical, as drying and chapping could result from prolonged exposure.
- For complete SDS, visit www.perimeter-solutions.com

ENVIRONMENTAL INFORMATION

SOLBERG FIRE-BRAKE PLUS™ Class A foam concentrate does not contain PFAS chemicals commonly found in fluorinated Class B foam concentrates. Perimeter Solutions foam manufacturing process is intentionally separated between fluorinated and non-fluorinated concentrate types, thus eliminating the potential for cross contamination or residual contamination.

PACKAGING

ORDERING INFORMATION				
SOLBERG FIRE-BRAKE PLUS	kgs*	Part #		
20 Litre Pail	22	AUFBPLUS20L		
200 Litre Drum	215	AUFBPLUS200L		
985 Litre Tote	1075	AUFBPLUS985L		

^{*}Approximate shipping weight

^{*}Contact your local authorized SOLBERG distributor or factory sales representative for additional details. https://perimeter-solutions.com





Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:

www.Perimeter-Solutions.com

UNITED STATES

10667 Jersey Blvd. Rancho Cucamonga, CA 91730 Tel: +1 800 682 3626

Tel: +1 909 983 0772

salesfoamusa@perimeter-solutions.com

EMEA

Polígono Industrial de Baiña, Parcela 23 33682 Baiña-Mieres (Asturias) – Spain

Tel: +34 985 24 29 45

salesfoamemea@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street St Marys NSW 2760 – Australia

Tel: +61 2 9673 5300

sales foamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.