

# PHOS-CHEK® LCE20W



## PRODUCT HIGHLIGHTS

- **USDA Forest Service 5100-304d certification**
- **100% phosphate product**
- **Low environmental footprint**
- **Low toxicity to fish**
- **Improved product stability**
- **Easy handling**
- **Low-viscosity**
- **Uncolored**
- **Second-generation product**
- **Reduced disposal costs**
- **Increased product safety**

## DESCRIPTION

**PHOS-CHEK® LCE20W** is an uncolored version of PHOS-CHEK LCE20-Fx long-term fire retardant, which is a red solution dropped from aircraft during active wildfires to prevent their spread. PHOS-CHEK LCE20W is a ground-applied fire retardant that is uncolored and can be delivered to application sites as a low-viscosity liquid. An innovative 100% phosphate product, PHOS-CHEK LCE20W utilizes an environmentally friendly formula to offer improved performance, product safety, and enhanced stability resulting in easier handling. A successor to PHOS-CHEK LC95W, this next-generation technology improves stability and is easier to handle and store. The updated formula also reduces environmental impact and disposal costs.



## APPLICATIONS

**PHOS-CHEK LCE20W** delivers a proactive and preventive wildfire management solution. This advanced fire retardant can be sprayed ahead of fire season or even during an oncoming fire threat with standard application equipment such as hydroseeders or tank sprayers. Anyone using equipment to spray fire retardant for ground applications can use PHOS-CHEK LCE20W, which is qualified by the USDA Forest Service under the updated specification for Long Term Retardant, Wildland Firefighting 5100-304d (published January 7, 2020). PHOS-CHEK LCE20W is also a useful tool for prescribed burns and fire breaks. When applied at lower concentrations, fire intensity can be dramatically reduced, while only slow and controlled burning remains supported.

As an uncolored fire retardant, PHOS-CHEK LCE20W offers all the wildfire prevention and protection benefits of PHOS-CHEK long-term fire retardant, but it can be applied in areas that are sensitive to staining, such as around homes or in national parks.

## PRODUCT CHARACTERISTICS

<b>Color</b>	<b>Uncolored</b>
<b>Mix Ratio</b>	<b>5.4:1 water/concentrate</b>
<b>Yield</b>	<b>1153 gal/ton of concentrate — 4811 liters/metric ton of concentrate</b>
<b>Concentrate Density</b>	<b>11.10 lb/gal — 1.330 kg/liter</b>
<b>Viscosity</b>	<b>150 – 400 centipoise (cP)</b>
<b>Refractive Index</b>	<b>9.5 – 12.0</b>

# PHOS-CHEK® LCE20W

APPLICATION	RETARDANT	GEL	FOAM	WATER
Indirect Attack	✓ ✓ ✓ ✓	✓ ✓	✓	
Direct/Parallel Attack	✓ ✓ ✓ ✓	✓ ✓ ✓	✓ ✓	✓
Interior Structure Attack		✓ ✓	✓ ✓ ✓ ✓	✓
Structure Protection: -Indirect Application	✓ ✓ ✓ ✓	✓ ✓ ✓	✓ ✓	✓
Structure Protection: -Direct Application		✓ ✓ ✓ ✓	✓ ✓ ✓	✓
Mop Up	✓ ✓	✓ ✓	✓ ✓ ✓ ✓	✓
Prescribed Burn Control	✓ ✓ ✓ ✓	✓ ✓ ✓	✓ ✓	✓

- ✓ ✓ ✓ ✓ = Superior Effectiveness
- ✓ ✓ ✓ = Excellent Effectiveness
- ✓ ✓ = Good Effectiveness
- ✓ = Baseline Effectiveness

## HANDLING PRECAUTIONS

- **FOR DETAILED SAFETY INFORMATION**, please refer to the SDS.
- **Non-irritating to eyes; non-irritating to skin.**
- **If in eyes:** flush with plenty of water.
- **Precautionary Measures:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary contact and removal of the material from the eyes, skin and clothing.
- **Eye Protection:** As with good industrial practices, the use of chemical goggles is recommended. Eye flushing equipment should also be available.
- **Skin Protection:** As with good industrial practices, protective gloves should be worn to minimize skin contact. Wash hands and contaminated skin after handling.
- **Respiratory Protection:** Avoid breathing vapor or mist.
- For detailed safety information, please refer to the SDS. [www.perimeter-solutions.com](http://www.perimeter-solutions.com)

## PACKAGING

ORDERING INFORMATION	Shipping Weight		Catalog #
PHOS-CHEK LCE20-Fx	lb.	kg.	
5 Gallon Pail (20 litres)	56	25	10001166
55 Gallon Drum (200 litres)	612	278	10001165
260 Gallon Tote (984 litres)	2894	1313	10001164
Bulk Packaging*	—	—	10000075

\*Contact your local authorized distributor or factory sales representative for additional details. <https://perimeter-solutions.com>



**Solutions That Save.**

### FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:

[www.Perimeter-Solutions.com](http://www.Perimeter-Solutions.com)

### UNITED STATES

10667 Jersey Blvd.  
Rancho Cucamonga, CA 91730  
Tel: +1 800 682 3626  
Tel: +1 909 983 0772

[salesfoamusa@perimeter-solutions.com](mailto:salesfoamusa@perimeter-solutions.com)

### EMEA

415, rue Louis Armand – Pôle d' Activités  
13290 Aix-en-Provence, Cedex 3  
France  
Tel: +33 (0)4 42 24 45 08

[salesretardantsemea@perimeter-solutions.com](mailto:salesretardantsemea@perimeter-solutions.com)

### ASIA PACIFIC

46 Hudson Crescent  
Lavington NSW 2641  
Australia  
Tel: +61 2 6040 6900

[retardants.APAC@Perimeter-Solutions.com](mailto:retardants.APAC@Perimeter-Solutions.com)

### CANADA

3060 Airport Road  
Kamloops, BC V2B 7X2  
Tel: +1 250 554 3530

[perimeter-solutions.com](http://perimeter-solutions.com)

**NOTICE** PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.