

# AQUAFILM™ EX-10

## AFFF ADDITIVE FOR FIRE EXTINGUISHERS (6-10%)



### DESCRIPTION

AFFF compound for extinction of hydrocarbon fires, especially designed for use in portable fire extinguishers. It attains very fast extinctions on light fuels, when it is applied as foam or spray, thanks to their improved aqueous film characteristics. In addition to the typical surfactants of AFFF, it contains special salts to increase the performance in solid fires.

### USE

Especially designed for use in portable fire extinguishers. Also it can be used with low expansion foam equipment (nozzles, monitors, foam chambers, etc) and non-aspirating devices (water spray nozzles and standard sprinklers).

### DOSAGE

The dilution rate is between 6% and 10% in water, depending on the desired efficiency. It can be used in premix (in portable extinguishers) or proportioned with standard equipments (in-line inductors, bladder tanks, balanced pressure systems, etc) and special purpose ones for AFFF agents (e.g. Hydrofoam nozzles).



### SPECIFICATIONS

CONCENTRATE		
Density @ 20°C, gr/cm <sup>3</sup>		1.13
pH @ 20°C		7
Viscosity, mPa.s	@ 20°C	12
Freezing point, °C		<-10°C

FOAM SOLUTION	
Dosage rate	6%
Surface tens. at 20°C, mN/m (Demineralised water)	16.5±0.5
Interfacial tens. with cyclohexane at 20°C, mN/m	1.5±0.5
Low Expansion Foam (EN 1568-3)	
Foam Expansion Index	8
25% Drainage Time, min:s	2:15

## PERFORMANCE

Its foam achieves a very quick knock-down of fires in spray applications and exhibits an excellent burn-back resistance. A 9 lit. hand extinguisher loaded with 6% solution of AQUAFILM EX-10 extinguishes easily the 233B fire test (7 m<sup>2</sup>) and between 21A and 27A class A fire. The performance of the product depends on the characteristics of the used extinguisher (pressure, nozzle, etc), thus the efficiency should be tested with the same fire extinguisher that will be used.

## PACKAGING

The product is supplied in 20 or 25 L PE prismatic containers, 200 L PE cylindrical drums and 1.000 L IBC containers.

## STORAGE

The concentrate should be stored at temperatures between -10° and +50°C, preferably in its original containers or in stainless steel or epoxy lined tanks. Do not mix with other foam concentrates without a previous verification of compatibility.

## ⚠ CAUTIONS

Foams should not be used in contact with electrical equipments, neither with chemical products that can react with water. It is recommended to avoid the contact of the foam concentrate with the skin. In case of eye splashes, wash with plenty of water. In case of ingestion do not induce vomit, drink water and take medical advice.



## Solutions That Save.

### FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:  
[www.Perimeter-Solutions.com](http://www.Perimeter-Solutions.com)

### UNITED STATES

1520 Brookfield Avenue  
Green Bay, WI 54313  
Tel: +1 (920) 593-9445  
[salesfoamusa@perimeter-solutions.com](mailto:salesfoamusa@perimeter-solutions.com)

### EMEA

Polígono Industrial de Baiña, Parcela 23  
33682 Baiña-Mieres (Asturias) – Spain  
Tel: +34 985 24 29 45  
[salesfoamea@perimeter-solutions.com](mailto:salesfoamea@perimeter-solutions.com)

### ASIA PACIFIC

3 Charles Street  
St Marys NSW 2760 – Australia  
Tel: +61 2 9673 5300  
[salesfoamapac@perimeter-solutions.com](mailto:salesfoamapac@perimeter-solutions.com)

[perimeter-solutions.com](http://perimeter-solutions.com)

**NOTICE** PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.