

MOBILE FOAM CART

FEATURES

- 2.5" X 1.5", 95 gpm inline eductor, mounted (64 mm X 38 mm, 360 /pm)
- 35 gallon (133 litres) stainless steel tank
- Heavy duty industrial 16.0" X 4.0" (406 mm X 102 mm) wheels and tires
- One person operation
- Rugged frame
- Two hose storage racks capable of holding 50 ft (15 m) fire hose

DESCRIPTION

The Perimeter Solutions Mobile Foam Cart is designed and constructed for one-person operation. This foam station can function at its full potential quickly in an emergency situation.

Foam concentrate is stored in a 35 gallon (133 litres) stainless steel tank equipped with a 95 gpm (360 lpm) eductor and pick-up tube. The pick-up tube is connected to the tank and utilizes a metering device to determine what percentage of foam concentrate is introduced into the water stream. On the inlet of the eductor, a supply fire hose is connected that delivers water from an independent source. A fire hose and discharge nozzle are connected to the outlet. When in operation, water flows through the eductor creating a vacuum that draws foam concentrate out of the tank to the metering valve of the eductor and into the water stream, delivering foam solution to the nozzle.

Note: gpm (lpm) of nozzle and eductor must match or unit will not operate as intended.

APPLICATION

The Perimeter Solutions Foam Cart is designed to provide firefighting capabilities to multiple hazard areas containing Class B fuels. Common high-hazard high-risk areas include:

- Flammable liquid storage
- Mining operations
- Paint storage areas
- Tank farms
- Wood manufacturing/processing areas



SPECIFICATIONS


The foam cart consists of a 35 gallon (133 litre) stainless steel foam concentrate tank with two fire hose storage compartments. The frame is constructed of stainless steel tube and angle. Eductor material is brass. The eductor is a 2.5" X 1.5" (64 mm X 38 mm) inline eductor with pick-up tube and metering valve for adjustment of 1 % to 6% proportioning. Two 50 ft (15 m) hose lengths are provided. The inlet hose is 2.5" X 50' (64 mm X 15 m) coupled and the outlet hose is 1.5" X 50' (38 mm X 15 m). Handline nozzles are not included. Handline nozzle capable of use with the foam cart could be medium expansion, air-aspirated or non-air aspirated nozzles with the same gpm (lpm) as the eductor.

OPTIONS

- 1.5" (38 mm) nozzle
- 1.5" X 50' hose (38 mm X 15 m)
- 2.5" X 50' hose (64 mm X 15 m)
- 95 or 125 gpm (360 or 473 lpm) by-pass manifold - stainless steel
- Hydrant-spanner wrench set
- For use with Solberg foam concentrates (RE-HEALING™, ARCTIC™, FIRE-BRAKE™)
- Vinyl cover

MOBILE FOAM CART

DIMENSIONAL INFORMATION



ORDERING INFORMATION

MOBILE FOAM CART		APPROXIMATE SHIPPING WEIGHT	
PART NO.	DESCRIPTION	lb	kg
33000	Mobile Foam Cart, Stainless Steel Tank, 35 gallon (133 litre), 95 gpm (360 lpm)	400	181



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:

www.Perimeter-Solutions.com

UNITED STATES

1520 Brookfield Avenue
Green Bay, WI 54313
USA
Tel: +1 920 593 9445
salesfoamusa@perimeter-solutions.com

EMEA

Polígono de Baiña, Parcela 23
33682 Mieres (Asturias)
Spain
Tel: +34 985 24 29 45
salesfoamemea@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street
St Marys NSW 0276 – Australia
Tel: +61 2 9673 5300
salesfoamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.